



BT-8800

Chemistry Analyzer

| Specifications |

Analysis method: Kinetic, end point, two point, dual wavelength, ABS
Light source: Halogen lamp, 6V/10W
Wavelength (nm): 340,405,492,510,546,578,630,700
Absorbance range: 0~4.0Abs
Wavelength accuracy: ± 2 nm
Spectrum band: ± 10 nm
Flowcell: 10mm quartz cell, 32 μ L volume
Temperature control: Room temperature , 37°C (± 0.1 °C variable)
Sampling volume: 100 μ L ~ 9999 μ L adjustable, recommended: ≥ 500 μ L
Cross contamination: $\leq 1.0\%$
Stability: ≤ 0.005 Abs/h
Memory: Up to 300 items and 30000 test results
Display: Large LCD touch screen display
Printer: Built-in thermal printer
Interface: Parallel port (For external printer) ,RJ-45,3USB,SDID,PS-2
Ambient: Room temperature: 10 °C ~ 32°C; Humidity: $\leq 40\%$ ~85%
Power: AC (110-220)V, 50Hz
Dimension: 362.5 x 341x 165mm (length * width * height)

- ✓ High-quality & close optical system
- ✓ Easy touch screen operation
- ✓ Convenient maintenance design
- Large memory capacity
- ✓ With 8 inner incubation positions
- ✓ Support barcode reader



7 inch touch screen



8 inner incubation positions

| Features |

- High-quality grating & close optical system
- Easy touch screen operation with 7 inch colour screen
- Convenient maintenance design
- Large memory capacity
- With 8 inner incubation positions
- Support barcode reader and keyboard